

NUDURA 12"  
(305mm) STANDARD  
FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POURS OR  
AS SPECIFIED

V-CLIP WALL PANEL  
ANCHOR

FORM PANELS c/w  
INSERT WEBS—CUT TO  
SUIT FLOOR  
CONNECTION—ADDITIONAL  
FORM SUPPORT AS  
REQUIRED

THROUGH WALL  
FLASHING AS PER CODE  
OR AS SPECIFIED

NUDURA 12" (305mm)  
SITE ASSEMBLED BRICK  
LEDGE FORM UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE  
COAT

NUDURA WATERPROOF  
MEMBRANE

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

FINISHED CONCRETE  
TOPPING

HOLLOW CORE  
PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD BENT  
INTO SHEAR KEY JOINT  
BETWEEN PANELS AS  
SPECIFIED

MASONITE BEARING  
PAD

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

### Non-Combustible Construction

Detail: Nudura 12" (305mm) Brick Ledge Form Unit, Hollow Core Precast Slab, Bearing Wall Detail, Brick Veneer Finish

File Name:

Drawn by: TVC

Scale: 1 : 8

Date: 12/21/2021

D12A02



Nudura Technical Support: 866-468-6299  
International: +1 705-726-9499

tremcoopg.com



Construction Products Group