

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

NUDURA 6" (152mm) STANDARD FORM UNIT

EPS CANT STRIP

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON CONCRETE SLAB

ADDITIONAL BRACING REQUIRED DURING ROOF SLAB POUR

WET SET DOWELS FIELD BENT INTO SLAB AS SPECIFIED

NUDURA 6" (152mm) HEIGHT ADJUSTER TIE

THERMAL BARRIER & INSULATED CONCRETE ROOF FORM INSTALLED AS PER MANUFACTURERS SPECIFICATIONS

WET SET DOWEL TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

1/2" (13mm) GYPSUM BOARD

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

**Non-Combustible Construction**

Detail: Nudura 6" (152mm) Form Unit, ICRS Connection, ICRS Resting on Form, Exterior Side Wall, Brick Veneer Finish

File Name:

Drawn by: TVC

Scale: 1 : 8

Date: 12/17/2021

F6D06



Nudura Technical Support: 866-468-6299  
International: +1 705-726-9499



Construction Products Group

tremcocpg.com