

FORM PANELS c/w INSERT
WEBS-CUT TO SUIT FLOOR
CONNECTION- ADDITIONAL
FORM SUPPORT AS
REQUIRED

U BRACKET ANCHOR
INSERT

GYPSUM BOARD
FINISHED/FIRE STOP
INSTALLED AT JOISTS
AS PER CODE

COMPOSITE STEEL
DECK-SLAB AND
REINFORCEMENT AS
SPECIFIED

OWSJ AND CONNECTION
SHOWN BEYOND TO
ALLOW FOR STAGGERING
OF JOISTS

OWSJ

WET SET DOWELS
FIELD BENT INTO
SLAB AS SPECIFIED

INTERIOR INSULATION
REMOVED AT JOIST
LOCATIONS

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

1/2" (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

NUDURA 8" (203mm)
STANDARD FORM UNIT

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 8" (203mm) Form Unit, Composite Steel Deck-Slab,
Steel Joist on Bearing Demising Wall

File Name:



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499

Drawn by: KS

Scale: 1 : 8

Date: 12/10/2021

G8C01



Construction Products Group

tremcocpg.com