

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

BRICK VENEER
c/w 1" (25mm)
AIR SPACE AND
BRICK TIES

THROUGH WALL
FLASHING AS
PER CODE OR
AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

STEEL LINTEL

FOAM BACKER
ROD AND
CONTINUOUS
CAULKING
AROUND FRAME
TO MASONRY

WINDOW FRAMING
BY OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

LINTEL
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

WOOD, VINYL, STEEL,
ETC. BUCK MATERIAL
FASTENING TO CONCRETE
w/ EMBEDDED SPIRAL
NAILS, BOLTS, SCREWS
IN STAGGERED PATTERN,
OR AS PER
MANUFACTURERS
SPECIFICATION

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
c/w FOAM
ROD/CAULK TO
SEAL TO INTERIOR
EDGE OF FRAME

THIS DETAIL IS SUITABLE FOR
NON-COMBUSTIBLE 1 TO 3 STOREY HIGH
APPLICATIONS AS PERMITTED UNDER LOCAL
CODES; FOR WINDOWS IN BRICK CLAD
MULTI-STOREY APPLICATIONS, REFER TO DETAIL
H6A04 & H6A05 UNDER THIS SECTION

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 6" (152mm) Form Unit, Window Head Detail,
Aluminum Framed Window, Wood Rough Buck, Brick Veneer Finish

File Name:

Drawn by: KS

Scale: 1 : 4

Date: 12/28/2021

H6A01



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499



Construction Products Group

tremcocpg.com