

FASTEN STUCCO MESH TO BUCK PRIOR TO PLACING BUCK AT JAMB CONDITION

1/2" (13mm) GYPSUM BOARD

NUDURA 6" (152mm) STANDARD FORM UNIT

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

DIRECT APPLIED ACRYLIC FINISH

OPENING REINFORCEMENT AS PER CODE OR AS SPECIFIED

DECORATIVE EPS FOAM TRIM APPLIED TO NUDURA FORM USING ADHESIVE

GYPSUM BOARD RETURN TO FRAME

ALUMINUM JAMB ANCHOR CLIPS

VAPOR BARRIER SEALED TO INTERIOR EDGE OF FRAME



WINDOW FRAME BY OTHERS

FOAM BACKER ROD AND CONTINUOUS CAULKING AROUND WINDOW FRAME c/w DRAIN SLOT AT CENTER OF SILL

1 1/2" (38mm) MIN. COVER

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

**Non-Combustible Construction**

 <p>Nudura Technical Support: 866-468-6299 International: +1 705-726-9499</p>	Detail: Nudura 6" (152mm) Form Unit, Window Jamb Detail, Aluminum Framed Window, Concrete Mounted, Exterior Finish as Specified		File Name:	 <p>Construction Products Group</p>
	Drawn by: KS	Scale: 1 : 4	Date: 12/28/2021	