

EXTERIOR FINISH AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

EXOAIR 230

FINISH GRADE MINIMUM 6" (152mm) OR AS PER CODE

2-3" MIN.

3/16" (5mm) ACRYLIC PARGE COAT OR OTHER APPROVED EPS COMPATIBLE FINISH

TREMPROOF 260

DRAINAGE, AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

BLOCKING BETWEEN JOISTS

JOISTS/TRUSSES AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

PROPRIETARY EMBEDDED JOIST ANCHORAGE SYSTEM OR EQUIVALENT

NUDURA STANDARD FORM UNIT

1/2" (13mm) GYPSUM BOARD

NOTE: SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH LOCAL CODES IS THE RESPONSIBILITY OF THE DESIGNER



Project:
Detail: Light Commercial Below Grade to Above Grade Transition

File Name:

LC-T-01

This detail is intended for conceptual purposes only.

Drawn by: KAB

Checked by: KS/RW/JS/CB

Scale: NTS

Date: 12/1/2020