



NUDURA 8" (203mm)
STANDARD FORM UNIT

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

EXTERIOR FINISH AS
SPECIFIED

HAUNCHED SLAB
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE
COAT

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

STEEL DOWELS TO MATCH
VERTICAL REINFORCEMENT IN
SLAB (EMBED 40x BAR
DIAMETER) INSTALLED AS
PER CODE OR AS SPECIFIED

FOAM FILL INTERLOCK GAPS
CONTINUOUS WITH NUDURA
LOW EXPANSION
POLYURETHANE SPRAY FOAM
BOTH INTERIOR AND
EXTERIOR

HAUNCHED SLAB ON GRADE

COMPACTED
GRANULAR

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Below Grade Construction

Detail: Nudura 8" (203mm) Form Unit Haunched Slab Detail
Exterior Finish As Specified Non-Insulated

File Name:

B8D02

Drawn by: T.V

Scale: 1 : 8

Date: 11/30/2021



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499



Construction Products Group

tremcocpg.com