



NUDURA 10" (254mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

V-CLIP WALL PANEL
ANCHOR

FORM PANELS c/w
INSERT WEBS-CUT TO
SUIT FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FINISHED CONCRETE
TOPPING

HOLLOW CORE
PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD
BENT AND GROUTED
INTO SHEAR KEY
JOINT BETWEEN
PANELS AS
SPECIFIED

MASONITE BEARING
PAD

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction



Detail: Nudura 10" (254mm) Form Unit, Hollow Core Precast Slab, Exterior Bearing Wall Detail, Exterior Finish as Specified			File Name:
Drawn by: JN	Scale: 1 : 8	Date: 12/21/2021	D10A01

