

NUDURA 10" (254mm)  
STANDARD FORM UNIT

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

ADDITIONAL BRACING  
REQUIRED DURING  
FLOOR SLAB POUR

BRICK VENEER c/w 1"  
(25mm) AIR SPACE  
AND BRICK TIES

WET SET DOWELS  
FIELD BENT INTO SLAB  
AS SPECIFIED

THROUGH WALL  
FLASHING AS PER CODE  
OR AS SPECIFIED

NUDURA 10" (254mm)  
SITE ASSEMBLED  
BRICK LEDGE FORM  
UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC  
PARGE COAT

NUDURA WATERPROOF  
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

CONCRETE SLAB

INSULATED CONCRETE FLOOR  
FORM INSTALLED AS PER  
MANUFACTURERS  
SPECIFICATIONS

THERMAL BARRIER AS PER  
FLOOR MANUFACTURERS  
SPECIFICATION



NUDURA 10"  
(254mm) HEIGHT  
ADJUSTER TIE

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT BETWEEN  
POURS OR AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

**Non-Combustible Construction**

 Nudura Technical Support: 866-468-6299 International: +1 705-726-9499	Detail: Nudura 10" (254mm) Form Unit, ICFS Connection, ICFS Resting on Form, Exterior Side Wall at Grade, Brick Veneer Finish	File Name:	 Construction Products Group
	Drawn by: TVC Scale: 1 : 8 Date: 12/21/2021	D10D11	