

NUDURA 'EZ' BUCK
w/ DIMENSIONAL
LUMBER AS SHOWN

1/2" (13mm)
GYPSUM BOARD

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

OPENING
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

BRICK RETURN TO
COVER AIR SPACE

ALTERNATIVE BUCK METHODS APPLIED:
WOOD, VINYL, STEEL, ETC. BUCK
MATERIAL FASTENED TO CONCRETE w/
EMBEDDED SPIRAL NAILS, BOLTS,
SCREWS IN STAGGERED PATTERN, OR
AS PER MANUFACTURERS SPECIFICATION

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

ALUMINUM JAMB
ANCHOR CLIPS

WINDOW FRAME
BY OTHERS



FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME
TO MASONRY c/w DRAIN
SLOT AT CENTER OF SILL

1 1/2"
(38mm) MIN.
COVER

THIS DETAIL IS SUITABLE FOR NON-COMBUSTIBLE 1 TO
3 STOREY HIGH APPLICATIONS AS
PERMITTED UNDER LOCAL CODES; FOR WINDOWS IN
BRICK CLAD MULTI-STOREY APPLICATIONS, REFER TO
DETAIL H6A04 & H6A05 UNDER THIS SECTION

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

 Nudura Technical Support: 866-468-6299 International: +1 705-726-9499	Detail: Nudura 6" (152mm) Form Unit, Window Jamb Detail, Aluminum Framed Window, Wood Rough Buck, Brick Veneer Finish		File Name:	 Construction Products Group
	Drawn by: KS	Scale: 1 : 4	Date: 12/28/2021	