

FASTEN STUCCO MESH TO BACK OF TEMPORARY BUCK TO ALLOW MESH TO BOND WITH CONCRETE

1/2" (13mm) GYPSUM BOARD

NUDURA 6" (152mm) STANDARD FORM UNIT

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

OPENING REINFORCEMENT AS PER CODE OR AS SPECIFIED

DRAINABLE EXTERIOR INSULATION FINISHING SYSTEM

GYPSUM BOARD RETURN TO FRAME

ALUMINUM JAMB ANCHOR CLIPS

VAPOR BARRIER SEALED TO INTERIOR EDGE OF FRAME

WINDOW FRAME BY OTHERS

1 1/2" (38mm) MIN. COVER

FOAM BACKER ROD AND CONTINUOUS CAULKING AROUND WINDOW FRAME c/w DRAIN SLOT AT CENTER OF SILL

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 6" (152mm) Form Unit, Window Jamb Detail, Aluminum Framed Window, Concrete Mounted, Drainable EIFS		File Name:
Drawn by: KS	Scale: 1 : 4	H6E08
Date: 12/29/2021		

