


TYPICAL CROSS SECTIONS B-1

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



TYPICAL WOOD FRAMED WALL &
ROOF ASSEMBLY AS PER CODE

EXTERIOR FINISH AS SPECIFIED

MIN. 6" (150mm) BELOW GRADE OF
ACRYLIC PARGE COAT

GRADE MIN. 2% SLOPE

NUDURA
WATERPROOFING
MEMBRANE

EXISTING SOIL
BACKFILL SOIL
AS PER CODE

NUDURA 6" (150mm) FORM
HORIZ/VERT REINFORCING AS
PER CODE OR AS SPEC'D IN
APPENDIX 'D' FOR BELOW GRADE

CONTINUOUS 4" (100mm)
ROUND PERFORATED DRAIN TILE
COVERED WITH 6" (150mm)
CRUSHED GRANULAR AS PER
CODE

OCT 15 2008

DTL-C2

ANCHORS BOLTS
INSTALLED
AS PER CODE

WOOD FLOOR
SYSTEM
AS SPECIFIED

1/2" (13mm)
GYPSUM BRD.

DTL-C1

CONTINUOUS CONCRETE FOOTING ON
UNDISTURBED SOIL AS PER CODE.
FOOTING SIZE AS PER CODE FOR
6" (150mm) CONC. BASEMENT WALL PLUS
ONE STORY FRAME WALL
(NON-BRICK FINISH & PREVAILING SITE
CONDITIONS)

WALL HEIGHT AS PER APP. 'D'
ABOVE GRADE TABLES

WALL HEIGHT AS PER APP. 'D'
BELOW GRADE TABLES

SLAB ASSEMBLY:
3" (75mm) CONCRETE FLOOR
2" (50mm) NUDURA FLOOR
TECHNOLOGY (OPTIONAL)
8" (200mm) CLEAR STONE



BUILDING SECTION
BASEMENT 6" (150mm) FORM
ONE STOREY WOOD FRAME
NON-BRICK FINISH

REV. NO.
004 KS

DWG NO.
B-1

REV. DATE:
SEPT 2008

DRAWN BY
J.N / N.L.

SCALE:
1/4"=1'-0"