

1/2" (13mm)
GYPSUM BOARD

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

OPENING
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

VERTICAL METAL
SIDING AS SPECIFIED

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

ALUMINUM JAMB
ANCHOR CLIPS

WINDOW FRAME
BY OTHERS

1 1/2"
(38mm) MIN.
COVER

FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME c/w
DRAIN SLOT AT CENTER OF
SILL

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

 Nudura Technical Support: 866-468-6299 International: +1 705-726-9499	Detail: Nudura 6" (152mm) Form Unit, Window Jamb Detail, Aluminum Framed Window, Concrete Mounted, Vertical Siding Finish		File Name:
	Drawn by: KS	Scale: 1 : 4	Date: 12/29/2021
<small>tremcoopg.com</small>			

