



NUDURA 6"
(152mm) STANDARD
FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

THROUGH WALL
FLASHING AND
WEEP HOLES AS
PER CODE OR AS
SPECIFIED

FINISHED GRADE
MINIMUM 6"
(152mm) OR AS
PER CODE (SEE
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT WHERE
EXTENDED ABOVE
GRADE

NUDURA
WATERPROOFING MEMBRANE

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

RIM JOIST

WOOD
JOISTS/TJI/TRUSSES
AS SPECIFIED

SHEAR BRACKET

SIMPSON STRONG
TIE (ICFVL)

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

NUDURA 6" (152mm)
BRICK LEDGE FORM
UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR
FROST PRONE AREAS. FOR ALTERNATIVE GRADE
LEVEL SEE DETAIL C6A34



NUDURA 6" (152mm) FORM UNIT SIMPSON LEDGER HANGER SYSTEM BRICK VENEER FINISH PARALLEL TO WALL	
REV. NO. 003 KS	DWG NO. C6A23
REV. DATE: AUGUST 2010	
DATE: T. VAN CLIEAF	SCALE: 1 : 8