

NUDURA 8" (203mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

WEEP HOLES AND  
THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

STEEL LINTEL c/w  
CONTINUOUS  
CAULKING AT FRAME

BRICK VENEER  
BEYOND

THRESHOLD

EXTERIOR CONCRETE  
SLAB AND SLOPE AS  
PER CODE

NUDURA 8"  
(203mm) BRICK  
LEDGE FORM UNIT  
BEYOND

NUDURA  
WATERPROOF MEMBRANE

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

1/2" (13mm) GYPSUM  
BOARD

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

STEEL DOOR FRAME  
c/w CAST IN  
ANCHORS

STEEL DOOR

FLOOR FINISH  
AS SPECIFIED

BLOCKING BETWEEN  
JOISTS

FLOOR  
JOISTS/TRUSSES  
AS SPECIFIED

PROPRIETARY  
EMBEDDED JOIST  
ANCHORAGE SYSTEM  
OR EQUIVALENT

1/2" (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
DOOR HEAD/SILL DETAIL  
BRICK VENEER FINISH  
WOOD ROUGH BUCK

REV. NO.  
003 KS

REV. DATE:  
SEPT 2010

DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
E8E03

SCALE:  
1 : 8