

NUDURA 6" (152mm)  
STANDARD FORM UNIT

BRICK VENEER c/w 1"  
(25mm) AIR SPACE  
AND BRICK TIES

WEEP HOLES AND  
THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

STEEL LINTEL AS  
SPECIFIED PER CODE

CONTINUOUS  
CAULKING AROUND  
FRAME AT CONTACT  
TO MASONRY

EXTENDED DOOR  
FRAME SCREWED  
DIRECTLY INTO NUDURA  
CONCRETE CORE

DOOR THRESHOLD

OPENING  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

EXTERIOR CONCRETE  
SLAB AND SLOPE AS  
PER CODE

$\frac{3}{16}$ " (5mm) ACRYLIC  
PARGE COAT

NUDURA 6"  
(152mm) BRICK  
LEDGE FORM UNIT

NUDURA WATERPROOFING  
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

LINTEL REINFORCEMENT  
AS PER CODE OR AS  
SPECIFIED

VAPOUR BARRIER  
SEALED TO FRAME

BLOCKING BETWEEN  
JOISTS

FLOOR FINISH  
AS SPECIFIED

PROPRIETARY  
EMBEDDED JOIST  
ANCHORAGE SYSTEM  
OR EQUIVALENT

FLOOR  
JOISTS/TRUSSES  
AS SPECIFIED

LAP VAPOR  
BARRIER TO  
CONTACT DOOR  
THRESHOLD

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



NUDURA 6" (152mm) FORM UNIT  
DOOR HEAD/THRESHOLD DETAIL  
BRICK VENEER FINISH

REV. NO. 000	DWG NO. E6E10
DATE: SEPT 2010	
DRAWN BY: K. STILL	SCALE: 1 : 8