



ENGINEERED FRAMING SYSTEM
BY PREBUCK LLC

PRE DRILLED COUNTERSUNK
ANCHOR OPENING

1/2" X 5" LDT REDHEAD CONCRETE ANCHOR
OR AS SPECIFIED

RIGID FOAM, BY OTHERS

TREMCO/DRYVIT AIR-WATER RESISTIVE
BARRIER COATING, IF SECIFIED
(REFER TO PRODUCT DATA SHEETS
FOR SPECIFIC APPLICATION METHODS)

3" MIN.

CONTINUOUS INSULATED
MASONRY WALL

ROOFING MEMBRANE,
BY OTHERS

NOTE: BUILDING FACADE NOT SHOWN FOR CLARITY

The architecture, engineering, and design of the project using the Prebuck products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Prebuck specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Prebuck to ensure you have the most recent version.

Parapet Caps

Detail: Parapet Cap, Cantilevered over CI Masonry Wall			
Drawn by: HDE	Checked by: BC	Scale: NTS	Date: 2/8/2022
www.tremcocpg.com			

File Name:	PB-PC-C-CIM
------------	-------------

