



ENGINEERED FRAMING SYSTEM
BY PREBUCK LLC

DYMONIC 100 OR
TREMCO APPROVED
EQUIVALENT

PRE DRILLED COUNTERSUNK
ANCHOR OPENING

RIGID FOAM, BY OTHERS

1/2" X 5" LDT REDHEAD CONCRETE ANCHOR
OR AS SPECIFIED

TREMCO/DRYVIT AIR-WATER RESISTIVE
BARRIER COATING, IF SECIFIED
(REFER TO PRODUCT DATA SHEETS
FOR SPECIFIC APPLICATION METHODS)

ROOFING MEMBRANE BY OTHERS
ROOFING MANUFACTURER MUST
CONFIRM ADHESION AND
COMPATIBILITY

CONTINUOUS INSULATED
STEEL STUD WALL

NOTE: BUILDING FACADE NOT SHOWN FOR CLARITY

The architecture, engineering, and design of the project using the Prebuck products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Prebuck specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Prebuck to ensure you have the most recent version.

Parapet Caps

Detail: Parapet Cap, Cantilevered over CI Steel Stud Wall

File Name:

PB-PC-C-CISS



Prebuck Technical Support: 616-309-6256

Drawn by: HDE

Checked by: BC

Scale: NTS

Date: 2/8/2022

www.tremcocpg.com



Construction Products Group