

1.5" (38.1 MM) THICK

PITCHED UP TO 24" (609.6 MM) WIDTH

ROOFING MEMBRANE BY OTHERS
ROOFING MANUFACTURER MUST
CONFIRM ADHESION AND
COMPATIBILITY

ENGINEERED FRAMING SYSTEM
BY PREBUCK LLC

NUDURA ICF OR
APPROVED EQUIVALENT

PRE DRILLED COUNTERSUNK
ANCHOR OPENING

1/2" X 5" LDT REDHEAD CONCRETE ANCHOR
OR AS SPECIFIED

TREMCO/DRYVIT AIR-WATER RESISTIVE
BARRIER COATING, IF SECIFIED
(REFER TO PRODUCT DATA SHEETS
FOR SPECIFIC APPLICATION METHODS)

NOTE: BUILDING FACADE NOT SHOWN FOR CLARITY

The architecture, engineering, and design of the project using the Prebuck products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Prebuck specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Prebuck to ensure you have the most recent version.

Parapet Caps



Detail: Parapet Cap, Flush over ICF Wall

File Name:

Drawn by: HDE

Checked by: BC

Scale: NTS

Date: 2/8/2022

PB-PC-F-ICF



Construction Products Group

Prebuck Technical Support: 616-309-6256

www.tremcocpg.com