

DAMP PROOF COURSE/  
AIR SHIELD MEMBRANE  
CONTINUOUS UNDER  
TOP PLATE EXTENDED  
TO COMPLETE AIR  
SHIELD WITH CEILING  
TECHNOLOGY

ROOF SHEATHING AS  
SPECIFIED

RAFTER

SOFFIT/FASCIA (TYPICAL)

38x140mm SILL PLATE  
ANCHORED TO CONCRETE AS  
PER CODE

HORIZONTAL/VERTICAL  
REINFORCEMENT AS  
SPECIFIED BY LOCAL  
PRESCRIPTIVE OR  
ENGINEERING DESIGN

NUDURA 152mm  
STANDARD FORM UNIT

EXTERIOR FINISH AS  
SPECIFIED

CEILING TECHNOLOGY  
ANGULAR CUT AT EDGE  
AND SEALED TO WALL  
WITH NUDURA SPRAY  
FOAM OR EQUIVALENT

PLASTER BOARD

PLASTER BOARD

2 LAYERS NUDURA  
CEILING TECHNOLOGY

POLYETHYLENE VAPOR  
BARRIER (CONTINUOUS)  
LAPPED AND SEALED TO  
NUDURA FORM

28x89mm FURRING STRIP  
(FACTORY EMBEDDED)  
400mm ON CENTRE

150mmx150mm AIR  
SHIELD MEMBRANE

PLASTER BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

*The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.*

**Typical Details CE-1**

Detail: Standard 152mm Form Unit Roof Rafter Detail At Top Plate  
Damp Proof Coursing Exterior Finish As Specified

File Name:

CE-14

Drawn by: K.S

Scale: 1 : 8

Date: 11/30/2021



Nudura Technical Support: 866-468-6299  
International: +1 705-726-9499



Construction Products Group

tremcocpg.com