

NUDURA 10" (254mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

ADDITIONAL BRACING
REQUIRED DURING
FLOOR SLAB POUR

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

WET SET DOWELS
FIELD BENT INTO SLAB
AS SPECIFIED

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

CONCRETE SLAB

INSULATED CONCRETE FLOOR
FORM INSTALLED AS PER
MANUFACTURERS
SPECIFICATIONS

THERMAL BARRIER AS PER
FLOOR MANUFACTURERS
SPECIFICATION

TEMPORARY STEEL
ANGLE

NUDURA 10" (254mm)
HEIGHT ADJUSTER TIE

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 10" (254mm) Form Unit, ICFS Connection, ICFS Resting on Form, Exterior Bearing Wall at Grade, Exterior Finish as Specified

File Name:

Drawn by: TVC

Scale: 1 : 8

Date: 12/21/2021

D10D10



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499



Construction Products Group

tremcocpg.com