

FORM PANELS c/w INSERT
WEBS—CUT TO SUIT FLOOR
CONNECTION— ADDITIONAL
FORM SUPPORT AS
REQUIRED

BRICK VENEER c/w 1"
(25mm) AIR SPACE
AND BRICK TIES

WET SET DOWELS FIELD
BENT INTO SLAB AS
SPECIFIED

U BRACKET ANCHOR
INSERT

THROUGH WALL
FLASHING AS PER
CODE OR AS SPECIFIED

$\frac{3}{16}$ " (5mm)
ACRYLIC PARGE COAT

NUDURA WATERPROOF
MEMBRANE

NUDURA 12" (305mm)
SITE ASSEMBLED BRICK
LEDGE FORM UNIT

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

GYPSUM BOARD
FINISHED/FIRE STOP
INSTALLED AT JOISTS
AS PER CODE

COMPOSITE STEEL
DECK—SLAB AND
REINFORCEMENT AS
SPECIFIED

OWSJ

INTERIOR INSULATION
REMOVED AT JOIST
LOCATIONS

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

NUDURA 12" (305mm)
STANDARD FORM UNIT

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 12" (305mm) Form Unit, Composite Steel Deck-Slab,
Steel Joist on Exterior Bearing Wall, Brick Veneer Finish

File Name:

Drawn by: TVC

Scale: 1 : 8

Date: 12/21/2021

D12C04



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499

tremcoopg.com



Construction Products Group