

NUDURA 6" (152mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

1 1/2"
(38mm) MIN.
COVER

STEEL LINTEL WITH
CONTINUOUS
CAULKING AROUND
FRAME TO MASONRY

BRICK VENEER
BEYOND

ALUMINUM
COMMERCIAL SIDE
LIGHT FRAME

EXTERIOR
CONCRETE
SLAB

COMPRESSIBLE FELT
FILLER STRIP

NUDURA 6" (152mm)
BRICK LEDGE FORM
UNIT BEYOND

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO CONCRETE

STEEL LINTEL AS
SPECIFIED (w/NELSON
STUDS OR BOLTS AS
PER OPENING
REQUIREMENTS)

FRAME ANCHOR CLIPS
SECURED TO CONCRETE
AND FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

NUDURA 6"
(152mm) DOUBLE
TAPER TOP FORM
UNIT OR HAND CUT
TAPER AT WIDTH
OF DOOR OPENING
(BOTH SIDES)

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 6" (152mm) Form Unit, Concrete Mounted, Aluminum Transom and Side Light at Head and Threshold, Brick Veneer Finish

File Name:

E6E06

Drawn by: TVC

Scale: 1 : 8

Date: 12/13/2021

tremcocpg.com



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499



Construction Products Group