

FASTEN STUCCO MESH
TO BACK OF
TEMPORARY BUCK TO
ALLOW MESH TO
BOND WITH CONCRETE

1/2" (13mm)
GYPSUM BOARD

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

DIRECT APPLIED
ACRYLIC FINISH

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

GYPSUM BOARD
RETURN TO FRAME

ALUMINUM JAMB
ANCHOR CLIPS

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

WINDOW FRAME
BY OTHERS

FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME
c/w DRAIN SLOT AT
CENTER OF SILL

1 1/2"
(38mm) MIN.
COVER

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 6" (152mm) Form Unit, Window Jamb Detail,
Aluminum Framed Window, Concrete Mounted, Direct Applied Acrylic Finish

File Name:

Drawn by: KS

Scale: 1 : 4

Date: 12/28/2021

H6C06



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499



Construction Products Group

tremcocpg.com