

ROOF SHEATHING AS SPECIFIED

ENGINEERED TRUSSES

ENGINEERED FRAMING SYSTEM BY PREBUCK LLC OR FUNCTIONAL EQUIVALENT

ANCHORAGE AS PER CODE OR SPECIFIED

SOFFIT/FASCIA AS PER CODE

CEILING TECHNOLOGY ANGULAR CUT AT EDGE AND SEALED TO WALL WITH NUDURA SPRAY FOAM

RIGID PANEL (1/2" (13mm) GYPSUM BOARD)

NUDURA 6" (152mm) STANDARD FORM UNIT

HORZ/VERT REINFORCEMENT AS PER CODE

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

1/2" (13mm) GYPSUM BOARD

2 LAYERS OF NUDURA CEILING TECHNOLOGY OR STANDARD ATTIC INSULATION AS PER CODE

6 MIL (0.15 mm) POLYETHYLENE VAPOR BARRIER (CONTINUOUS) LAPPED AND SEALED TO NUDURA FORM

1x4 (28mmx89mm) FURRING STRIP (FACTORY EMBEDDED) (16" (400mm) c/c)

6x6 (152mmx152mm) AIR SHIELD MEMBRANE

1/2" (13mm) GYPSUM BOARD

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

### Combustible Construction

Detail: Nudura 6" (152mm) Form Unit, Nudura Ceiling Technology, Brick Veneer Finish, Roof Rafters

File Name:



Drawn by: JN

Scale: 1 : 8

Date: 3/16/2022

F6B02



Nudura Technical Support: 866-468-6299  
International: +1 705-726-9499

www.tremcocpg.com

Construction Products Group