



EXTERIOR FINISH  
AS SPECIFIED

WET SET DOWELS  
TO MATCH  
VERTICAL  
REINFORCEMENT  
BETWEEN POURS  
OR AS SPECIFIED

NUDURA 6" (152mm)  
STANDARD FORM  
UNIT

$\frac{3}{16}$ " (5mm)  
ACRYLIC PARGE  
COAT

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

CONCRETE SLAB

GRANULAR FILL

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**  
INTEGRATED BUILDING TECHNOLOGY  
*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
STEM WALL AT SLAB ON GRADE  
EXTERIOR FINISH AS SPECIFIED  
NON-INSULATED

REV. NO. 004 KS	DWG NO. B6C01
REV. DATE: FEB 2010	
DRAWN BY: N. LEMMON	SCALE: 1 : 8