

NUDURA 12" (305mm)  
STANDARD FORM UNIT

BRICK VENEER c/w 1"  
(25mm) AIR SPACE  
AND BRICK TIES

WET SET DOWELS  
TO MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POUR OR  
AS SPECIFIED

THROUGH WALL  
FLASHING AND  
WEEP HOLES AS  
PER CODE OR AS  
SPECIFIED

FINISHED GRADE  
MINIMUM 6"  
(152mm) OR AS  
PER CODE (SEE  
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC  
PRIME COAT WHERE  
EXTENDED ABOVE  
GRADE

NUDURA  
WATERPROOFING MEMBRANE

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

SUB FLOOR

FLOOR  
JOISTS/TRUSSES  
AS SPECIFIED

PROPRIETARY  
EMBEDDED JOIST  
ANCHORAGE SYSTEM  
OR EQUIVALENT

NUDURA 12"  
(305mm) BRICK  
LEDGE FORM UNIT

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR  
FROST PRONE AREAS. FOR ALTERNATIVE GRADE  
LEVEL SEE DETAIL C6A30



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 12" (305mm) FORM UNIT  
MULTI-PURPOSE HANGER  
BRICK VENEER FINISH

REV. NO.  
004 KS  
REV. DATE:  
AUGUST 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
C12A08  
SCALE:  
1 : 8