

ROOF SHEATHING AS SPECIFIED

ENGINEERED TRUSSES

2x6" (38x140mm) SILL PLATE ANCHORED TO CONCRETE AS PER CODE

SOFFIT/FASCIA AS PER CODE

CEILING TECHNOLOGY ANGULAR CUT AT EDGE AND SEALED TO WALL WITH NUDURA SPRAY FOAM

RIGID PANEL (1/2" (13mm) GYPSUM BOARD)

NUDURA 6" (152mm) STANDARD FORM UNIT

1/2" (13mm) GYPSUM BOARD

HORZ/VERT REINFORCEMENT AS PER CODE

2 LAYERS OF NUDURA CEILING TECHNOLOGY OR STANDARD ATTIC INSULATION AS PER CODE

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

6 MIL (0.15 mm) POLYETHYLENE VAPOR BARRIER (CONTINUOUS) LAPPED AND SEALED TO NUDURA FORM

1x4 (28mmx89mm) FURRING STRIP (FACTORY EMBEDDED) (16" (400mm) c/c)

6x6 (152mmx152mm) AIR SHIELD MEMBRANE

1/2" (13mm) GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH LOCAL CODES IS THE RESPONSIBILITY OF THE DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
NUDURA CEILING TECHNOLOGY
BRICK VENEER FINISH
ROOF RAFTERS

REV. NO.
007 KS
REV. DATE:
MARCH 2012
DRAWN BY:
J. NEILON

DWG NO.
F6B02
SCALE:
1 : 8