



NUDURA 10" (254mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

V-CLIP WALL PANEL
ANCHOR

FORM PANELS c/w
INSERT WEBS-CUT TO
SUIT FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

3/16" (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

1/2" (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FINISHED CONCRETE
TOPPING

HOLLOW CORE
PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD
BENT AND GROUTED
INTO SHEAR KEY
JOINT BETWEEN
PANELS AS
SPECIFIED

MASONITE BEARING
PAD

1/2" (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA 10" (254mm) FORM UNIT
HOLLOW CORE PRECAST SLAB
EXTERIOR BEARING WALL DETAIL
EXTERIOR FINISH SPECIFIED

REV. NO.
003 KS
REV. DATE:
FEB 2010
DRAWN BY:
J. NEILON

DWG NO.
D10A01
SCALE:
1 : 8