

FORM PANELS c/w INSERT
WEBS—CUT TO SUIT FLOOR
CONNECTION— ADDITIONAL
FORM SUPPORT AS
REQUIRED

BRICK VENEER c/w 1"
(25mm) AIR SPACE
AND BRICK TIES

WET SET DOWELS FIELD
BENT INTO SLAB AS
SPECIFIED

U BRACKET ANCHOR
INSERT

THROUGH WALL
FLASHING AS PER
CODE OR AS SPECIFIED

$\frac{3}{16}$ " (5mm)
ACRYLIC PARGE COAT

NUDURA WATERPROOF
MEMBRANE

NUDURA 8" (203mm)
PRE-ASSEMBLED BRICK
LEDGE FORM UNIT

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

GYPSUM BOARD
FINISHED/FIRE STOP
INSTALLED AT JOISTS
AS PER CODE

COMPOSITE STEEL
DECK—SLAB AND
REINFORCEMENT AS
SPECIFIED

OWSJ

INTERIOR INSULATION
REMOVED AT JOIST
LOCATIONS

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

NUDURA 8" (203mm)
STANDARD FORM UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
COMPOSITE STEEL DECK—SLAB
STEEL JOIST ON EXT. BEARING WALL
BRICK VENEER FINISH

REV. NO.
004 KS
REV. DATE:
MARCH 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
D8C06
SCALE:
1 : 8