

NUDURA 12" (305mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

FORM PANELS c/w
INSERT WEBS-CUT TO
SUIT FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

WET SET FIELD DOWELS
FIELD BENT INTO SLAB
AS SPECIFIED

$\frac{3}{16}$ " (5mm)
ACRYLIC PARGE COAT

NUDURA WATERPROOF
MEMBRANE

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR AS
SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

STEEL DECK SUPPORT
WELDING ANCHOR
INSERT

COMPOSITE STEEL
DECK- SLAB AND
REINFORCEMENT AS
SPECIFIED

INTERIOR INSULATION
TO BE DISCONTINUOUS
AT FLOOR LINES

OWSJ

MINIMUM $\frac{1}{32}$ " (0.8mm) x 2
 $\frac{1}{2}$ " (63.5mm) GALVANIZED
STEEL CHANNEL CAP TO
PROVIDE THERMAL BARRIER
PROTECTION

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
COMPOSITE STEEL DECK-SLAB
STEEL JOISTS ON SIDE WALL
EXTERIOR FINISH AS SPECIFIED

REV. NO.
004 KS
REV. DATE:
MARCH 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
D12C02
SCALE:
1 : 8