

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

EPS CANT STRIP

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON 3 1/2" (89mm) RIGID INSULATION

V-CLIP WALL PANEL ANCHOR

FORM PANELS c/w INSERT WEBS-CUT TO SUIT ROOF CONNECTION-ADDITIONAL FORM SUPPORT AS REQUIRED

MASONITE BEARING PAD

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

HOLLOW CORE PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD BENT AND GROUTED INTO SHEAR KEY JOINT b/n PANELS AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

NUDURA 10" (254mm) STANDARD FORM UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
HOLLOW CORE PRECAST ROOF
EXTERIOR BEARING WALL DETAIL
BRICK VENEER FINISH

REV. NO.
003 KS
REV. DATE:
APRIL 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
F10E02
SCALE:
1 : 8