

NUDURA 8" (203mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

WEEP HOLES AND  
THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

STEEL LINTEL c/w  
CONTINUOUS  
CAULKING AT FRAME

BRICK VENEER  
BEYOND

THRESHOLD

COMPRESSIBLE  
FELT FILLER  
STRIP

NUDURA 8"  
(203mm) BRICK  
LEDGE FORM UNIT  
BEYOND

1/2" (13mm) GYPSUM  
BOARD

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

STEEL DOOR FRAME  
c/w CAST IN  
ANCHORS

STEEL DOOR

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

FLOOR FINISH  
AS SPECIFIED

CONCRETE  
FLOOR SLAB  
ON GRADE

NUDURA 8" (203mm)  
DOUBLE TAPER TOP  
FORM UNIT OR HAND  
CUT TAPER AT WIDTH  
OF DOOR OPENING  
(BOTH SIDES)

HORIZ/VERT  
REINFORCEMENT  
AS PER CODE  
OR AS SPECIFIED

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
STEEL DOOR AT HEAD/THRESHOLD  
BRICK VENEER FINISH  
DIRECT ATTACHED

REV. NO.  
004 KS  
REV. DATE:  
SEPT 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
E8H05  
SCALE:  
1 : 8