

NUDURA 12" (305mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL c/w
CONTINUOUS
CAULKING AT FRAME

BRICK VENEER
BEYOND

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

STEEL DOOR

THRESHOLD

EXTERIOR
CONCRETE SLAB

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

NUDURA FORM
PANELS c/w INSERT
WEBS-CUT TO SUIT
CONCRETE CAP
PLACEMENT-ADDITIONAL
FORM SUPPORT AS
REQUIRED

CONCRETE
FLOOR SLAB
ON GRADE

COMPRESSIBLE
FELT FILLER
STRIP

NUDURA 12"
(305mm) BRICK
LEDGE FORM UNIT
BEYOND

EPS FOAM CUT DOWN
THICKNESS OF INTERIOR
SLAB AT EXTENT OF
DOOR OPENING WIDTH

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
STEEL DOOR AT HEAD/THRESHOLD
CONCRETE CAP AT THRESHOLD
BRICK VENEER FINISH
DIRECT ATTACHED

REV. NO.
000

REV. DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E12H08

SCALE:

1 : 8