



# TECHNICAL DATA SHEET

# HORIZON<sup>®</sup> COATING SYSTEM

Topcoat For Exterior Above-Grade Walls

## TWO-PART BARRIER SYSTEM

- Your Tremco below-grade exterior waterproofing system protects your foundation from leaks and seepage, and if insulated, interior condensation.
- The Horizon Coating System continues your waterproofing protection from the grade line to the sill plate and beautifies the exterior of your poured or block foundation wall.

## PROTECTION FROM FOOTING TO SILL

- The Horizon Coating System starts with proven below-grade foundation waterproofing protection offered by Tremco.
- The Horizon Coating System is completed with your choice of highly durable Horizon Coarse Coat or Horizon Matte Coat from the grade-line to the sill plate. Horizon Coarse Coat provides a more textured finished look, while Horizon Matte Coat offers a smoother clean-looking finish to your exterior above-grade walls. With either UV-resistant finish coat, the Horizon Coating System meets the below-grade waterproofing system at the grade line, completing the full-wall waterproofing protection and eliminating the troubleshooting grade-line spot at which the majority of wall leaks occur.

## SYSTEM HISTORY

Horizon Foundation Finishing Systems come from Tremco, with a heritage in spray-applied barrier technology stretching back more than 30 years. Since 1983, our team has sparked innovations in fluid membrane formulations and performance.

And we offer more than three decades of experience installing spray-applied barriers – including the TUFF-N-DRI<sup>®</sup> basement Waterproofing System, the #1 brand of new basement waterproofing in North America.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	DESCRIPTION	METHOD
Type	Elastomeric, emulsion-based coating	
Color	Grey	
Density	8.3 lbs/gal	
Application Temperature	32°F (0°C) to 100°F (38°C)	
Cure Time	24 hours	
Film Thickness	40 mils dry @ 25ft <sup>2</sup> /gal	
Elongation	150%	ASTM D2370
Mandrel Bend	½" @ -15°F (-26°C)	ASTM C711
Water Vapor Permeance	6 perms	ASTM E96
	<b>MATTE FINISH</b>	<b>COARSE FINISH</b>
Solids	63 ± 2 [percent by weight]	72 ± 2 [percent by weight]
Density	8.2 ± .4 lb/gal	10.0 ± .5 lb/gal
Application	Airless spray/brush	Air atomized texture spray/brush

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE:** All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

HCS-DS/0223

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



*Construction Products Group*

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)