

---

### PRODUCT DESCRIPTION

A ¼" (6mm) coarse thread #10 (5mm) Hex Head Screw with Steel Flat Washer available in three standard lengths; 2", 2 ½", and 3" (51 mm, 64 mm, and 76 mm). These screws are zinc plated and come with a floating steel flat washer to prevent the screw head from piercing through the material it's being fastened to. Two ¼" (6mm) nut drivers are included in each pail of hex head screws.



---

### BASIC USES

The Hex Head Screw is used for multiple applications on the job site. These include securing the alignment system to the forms, for use with the Nudura One Series, and attachment of strapping or buck material to the wall.

---

### LIMITATIONS

The Nudura Hex Head Screws are not suitable for permanent installation in an exterior application.

---

### AVAILABILITY

The Hex Head Screws and Flat Washers come in three lengths: 2" (50 mm), 2 ½" (64 mm), and 3" (76mm). Also, each pail of hex head screws includes two ¼" (6mm) nut drivers.

---

### PACKAGING

The Hex Head Screws are packaged 1,000 pieces in a durable clear plastic pail.

- Box Length: 9" (229 mm)
- Box Width: 9" (229 mm)
- Box Height: Varies- 5" (127 mm) to 8" (203 mm)
- Box Weight: Varies- 14 lbs (6 kg) to 18 lbs (8 kg)

---

### STORAGE

Store the Hex Head Screws in their original, undamaged packaging within a clean and dry storage area.

Please refer to our website at [www.nudura.com](http://www.nudura.com) for the most up-to-date Product Data Sheets.

**NOTE:** All Nudura Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

NHHS-DS/1025