

PRODUCT DESCRIPTION

Nudura's T-Form Support Strap is a 24" long x 1 ½" wide (610 mm x 38 mm) 16-gauge galvanized steel strap created to support site cut Nudura forms at a T-intersection. The T-Form Support Strap is designed to hook over the internal horizontal reinforcement bar in the main wall of a T-intersection and be secured to the fastening strips in the 'T' portion of the wall. The Nudura T-Form Support Strap allows the installation of a T-intersection anywhere along the length of a wall, requiring less time to install than a pre-manufactured T-Form, and can help to reduce vertical stack joints in a wall. The straps can be left in place following the concrete pour, or easily cut off if required.



BASIC USES

The T-Form Support Strap is designed to support Nudura forms when site cutting T-intersections using standard Nudura forms. Nudura T-Form Support Straps are installed with two straps on both sides of each course of forms (Four straps per form). A minimum of two of Nudura's #10 x 2" (51 mm) Hex Head Screws are recommended to be installed into each strap. Depending on site conditions, once the concrete is cured the T-Form Support Strap can be left in place or cut off if required. For complete installation instructions please refer to Nudura's website at <http://www.nudura.com>.

FEATURES & BENEFITS

- Manufactured from durable 16-gauge galvanized steel
- Easily installed at any position in the length of a wall to create a T-intersection
- Can remain in place or cut off if required

AVAILABILITY

Nudura's T-Form Support Strap is available from your local Nudura distributor. For Distributor locations, visit <https://www.nudura.com/>

PACKAGING

Nudura's T-Form Support Strap is packaged 30 pieces in a durable, cardboard box.

- Box Length: 24" (610 mm)
- Box Width: 3" (76 mm)
- Box Height: 3" (76 mm)
- Box Weight: 16 lbs (7 kg)

STORAGE

Store the T-Form Support Straps in their original, undamaged packaging in a clean, dry location.

ESTIMATING

To estimate the quantity of T-Form Support Straps (NUS ATSTP 00) required for a specific project, begin by determining the number of courses in the height of the wall. Multiply the number of courses by 4, and then multiply by the number of T-connections in the project.

To estimate the quantity of Nudura's #10 x 2" (51 mm) Hex Head Screws (NUS ASHEX 20) multiply the number of T-Form Support Straps by 2. This will estimate for 2 screws per T-Form Support Strap.

Calculations

TSTRAP = (# of courses x 4) x # of T-connections

Screws = TSTRAP x 2

Please refer to our website at www.nudura.com for the most up-to-date Product Data Sheets.

NOTE: All Nudura Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TFSS-DS/0225

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



nudura.com | 866.468.6299



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com